

TAP POSITION INDICATOR TC-02



FEATURES:

- Static design, no moving parts.
- Quick Response Time.
- Output independent of load impedance.
- Components have high thermal withstand capacity & can survive extreme tropical atmospheric conditions.
- Galvanic isolation between input / output /auxiliary power supply.
- Standard Flush mounting, cabinets.
- On site programmable any parameter.

FRONT

GENERAL SPECIFICATIONS:

#	SPECIFICATION	
1	Manufacturer.	ACCORD ELECTRO-TECHNICS PVT. LTD.
2	Model No.	TC-02.
4	Aux Power Supply	90 – 270 V AC/DC OR 48V DC
5	Input	Resistor chain 1k x user defined.
6	Output	4-20 mA DC Dual output
7	Communication Port	RS 485, 2WIRE (optional) On MODBUS RTU Protocol.
8	Accuracy Class	+0.5 % of full span.
9	Display	Two nos. of 1" FND Seven Segment Display for Tap Indication
10	Front Key Board	Three Keys are provided on front side for settings.
11	Size	96 x 96 x 110 mm.
12	Cut Out Size	90 x 90 mm.
13	Mounting	Flush
14	Operating Temperature Range.	0-55°C
15	Terminals.	Suitable for 2.5 mm ² wires.

BACKPLATE STICKER AND CONNECTION:

